

Sessel Nr. 14^{1/2}

38 cm Durchmesser

Schnittmaterial: Backelschluß 125 cm lang, 40×38 mm stark

} 35 mm stark (roh gebogen Nr. 14^{1/2})


W

Varianten:


Siehe Drehstockerl Nr. 5001

„ „ „ 5036

„ Stockerl „ 4812



Nr.	findet Anwendung bei:			Normale Ausführung	Geflechts-		Notizen
	Sessel Nr.	Fauteuil Nr.	div. Möbel Nr.		Gattung	Maschenweite	
14 ^{1/2}	14 ^{1/2} , 15 ^{1/2} , 18 ^{1/2} , 31 ^{1/2} , 45 ^{1/2} , 52 ^{1/2} , 54 ^{1/2} , 85 ^{1/2} , 92 ^{1/2} , 93 ^{1/2} , 94 ^{1/2} , 95 ^{1/2} , 98 ^{1/2} , 124 ^{1/2} , 149 ^{1/2} , 260 ^{1/2}			Gewöhl. Geflecht	3H ^{II}	14 ^{1/2} mm	
	100 ^{1/2} , 142 ^{1/2} , 249 ^{1/2} , 381 ^{1/2}			Holzstz			
KBWR							



Sessel Nr. 28

36×38 cm

Schnittmaterial 125 cm lang, 40×38 mm stark

} 35 mm stark (roh gebogen Nr. 28)

W

Nr.	findet Anwendung bei:			Normale Ausführung	Geflechts-		Notizen
	Sessel Nr.	Fauteuil Nr.	div. Möbel Nr.		Gattung	Maschenweite	
28	28			Gewöhl. Geflecht	3H ^{II}	14 mm	
KR							